



VISION Rechargeable Products
Sealed Lead Acid Battery

www.vision-batt.com

HP&HF Series

High Rate Discharge

The new VISION HP/HF series batteries are specially designed for applications where need high power output. By optimum design of battery grids and plate paste formula, the HP/HF series can deliver up to 40% more power than VISION standard CP/FM series.

Shenzhen Center power tech co., Ltd has more than 15 year's experience in the manufacturing of VRLA batteries. SZCPT is one of the biggest manufacturers of SLA (or VRLA) batteries in the world, the biggest one in Mainland China and the first in China to develop and commercialize the sealed lead-acid battery with brand name VISION and has been at the forefront of battery technology from day one.

SZCPT leads the world in innovative battery technology. Our global network of sales and service engineers, backed in turn by our agents and distributors, means that we are currently active in more than 100 countries.


Shenzhen Center Power Tech. Co., Ltd

HF12-560W-X 12V 120Ah

(Edition Jan 2014)

General Features

- Positive and negative plates in lead-calcium tin alloy
- Superior energy density
- Operates at a low internal pressure.
- Gas Recombination
- Usable in any orientation
- A recognized component of UL
- Very high power output
- Application specific designs
- A couple Range from 13W to 890W per cell for 10' @ 1.60Vpc
- Six months shelf life at 20°C
- Design life 10 years



Dimensions and Weight

	SI Units	English Units
Length	410mm	16.1inch
Width	176mm	6.93inch
Height	224mm	8.82inch
Total Height	224mm	8.82inch
Approx. Weight	37.7Kg	83.1lbs

Performance Characteristics

- Nominal Voltage 12V
- Number of cell 6
- Nominal Capacity 77 °F(25°C)
 - 10 min wattage @1.6V 560W/cell
 - 20 hour rate (6.57A, 10.5V) 131Ah
- Nominal Capacity 77°F(25°C)
 - 10 hour rate (12.0A, 10.8V) 120Ah
- Internal Resistance
 - Fully Charged battery 77°F(25°C) \leq 4.0mOhms
- Self-Discharge
 - 3% of capacity declined per month at 20°C(average)
- Operating Temperature Range
 - Discharge -20~60°C
 - Charge -10~60°C
 - Storage -20~60°C
- Max. Discharge Current 77°F(25°C) 950A(5s)
- Charge Methods: Constant Voltage Charge 77°F(25°C)
 - Cycle use 2.40-2.45VPC
 - Maximum charging current 36A
 - Temperature compensation -30mV/°C
- Standby use 2.20-2.30VPC
 - Temperature compensation -20mV/°C



Center Power Industrial Park, Tongfu Industrial District Dapeng Town, 518120 Shenzhen, China
Tel: 86 755 8431 8088 Fax: 86 755 8431 8038 E-mail: sales@vision-batt.com
Website: <http://www.vision-batt.com>

HF12-560W-X 12V 120Ah

Discharge Data

Constant Current Discharge Data (Amperes at 25°C)

End Voltage Per cell / V	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	60min
1.60	314	260	212	184	165	144	129	117	107	98.4	91.6
1.65	297	246	201	175	157	137	122	111	101	93.8	87.4
1.70	280	233	190	165	148	130	116	105	96.3	89.2	83.2
1.75	263	219	179	156	140	122	110	99.5	91.3	84.6	79.0
1.80	253	211	174	151	136	119	107	97.1	89.1	82.6	77.2

Constant Power Discharge Data (Watts per cell at 25°C)

End Voltage Per cell / V	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	60min
1.60	560	460	376	326	292	258	232	212	195	181	169
1.65	539	444	363	315	283	250	225	206	189	176	164
1.70	518	428	351	304	273	242	218	200	184	170	160
1.75	497	412	338	293	264	233	211	193	178	165	155
1.80	476	396	325	282	254	225	204	187	172	160	150

(Note)The above characteristics data are average values obtained within three charge/discharge cycles not the minimum values. All data shall be changed without notice, Vision reserves the right to explain and update the information contained hereinto.

Performance drawings

